

Powergame+™ Platform

Outdoor Installation Base · Mat 2.0 Systems

OUTDOOR ONLY



The essential technical base for any outdoor Mat 2.0 installation.

KEY FEATURES

- I Ground Isolation**
Raises mats by 19 mm — protects against moisture, mud and outdoor debris.
- D High-Performance Drainage**
Permeability > 360 mm/h (EN 12616) — no standing water even in heavy rain.
- R Quick Assembly**
Tool-free click-and-lock system. Tiles and profiles assemble in minutes.
- C 10 Configurations**
Covers 1 to 10 Mat 2.0 mats — from 1.12 m² to 6.70 m² depending on configuration.

TECHNICAL SPECIFICATIONS

Tile	305 × 305 × 19 mm — Polypropylene
Shock absorption	EN 14808 : >= 11 %
Vertical rebound	EN 12235 : 100 %
Drainage	EN 12616 : > 360 mm/h
UV resistance	EN ISO 20105-A02 : >= 3
Tensile strength	1,312 N
Configurations	10 formats — 1 to 10 Mat 2.0 mats
Material	Black polypropylene (PP)

INSTALLATION & USE

- 1 Check the ground**
Flat, stable and compact surface. Treat any unstable ground before installation.
- 2 Assemble the tiles**
Clip tiles row by row. Attach male and female edge profiles, then corners.
- 3 Place Mat 2.0 mats**
Lay mats on the assembled platform. Orient the connector and plug in the cables.
- 4 Cover with OUTDOOR mat**
Deploy the protective mat (see OUTDOOR mat sheet). Check 300 mm overhang.