

Communication Gateway

Model M2G10 · Mat 2.0 Systems

GATEWAY



Built-in WiFi, Ethernet and 4G — secure real-time data transmission.

KEY FEATURES

C Triple Connectivity
WiFi, Ethernet and 4G. Seamless connection for any environment.

A Autonomous
Built-in NiMH shutdown battery. Operates independently and securely.

P Plug & Play
Quick setup via the Technis Counting app. No technical expertise required.

S Secure
Encrypted data transmission. No personal data collected or stored.

TECHNICAL SPECIFICATIONS

Length	156 mm / 6.14 in
Width	177 mm / 6.97 in
Height	97 mm / 3.82 in
Weight	610 g / 1.34 lb
Connectivity	WiFi · Ethernet · 4G
Ethernet class	10BASE-T / 100Base-TX, CAT5
Supply voltage	220-240 VAC, 50-60 Hz
Max. power	30 W
Consumption (24h)	0.72 kWh
Battery	3.6 V, 800 mAh, NiMH
Operating temp.	0-50°C / 32-122°F
Certifications	CE · FCC · EN 62368-1

INSTALLATION & USE

- 1 Connect the mats**
Connect the Mat-to-Gateway connector cable to the 'Mat Connector' port on the gateway.
- 2 Power the gateway**
Plug the supplied power cable into a grounded 220-240 VAC outlet.
- 3 Scan the QR code**
Open Technis Counting app. Go to Admin > Scan QR code, aim at the rear panel.
- 4 Set up counting**
Name the device, select the installation, passage and counting direction.